

WHAT IS CLAIMED IS AS FOLLOWS:

1. A cable clip comprising:

an outer housing including a first end with an inner edge and an outer edge, a second end with an inner edge and an outer edge, and a side with an inner edge and an outer edge, the inner edges of the first end, the second end and side defining an open sided space;

the outer housing including a trumpet flare to provide bend radius protection for telecommunications cables received in the open sided space;

a gate hingedly mounted to the first end and movable to a closed position across the open sided space and releasably attached to the second end

the outer edges of the first end, the second end and the side including first, second and rear grooves, respectively, for receiving a first edge, a second edge and a rear edge, respectively, of a mounting opening, the first and second grooves having recesses for receiving a tab formed in each of the first and second edges of the mounting opening.

2. The cable clip of claim 1, wherein the gate is hingedly attached at the first end by a living hinge, the gate including a catch which is adapted to receive and releasably engage a latch at the second end, the gate covering the open sided space when in a closed position with the latch engaging the catch, and the gate being movable to an open position upon disengaging the latch from the catch.

3. The cable clip of claim 2, wherein the gate includes a curved inner surface and at least one support rib on an opposite outer surface.

4. The cable clip of claim 2, wherein the gate includes a first shoulder adjacent the catch and the second end includes a first extension adjacent the latch, the first extension engaging the first shoulder when the gate is in the closed position.

5. The cable clip of claim 4, wherein the gate includes a second shoulder adjacent the catch opposite the first shoulder and the second end includes a second extension

adjacent the latch opposite the first extension, the second extension engaging the second shoulder when the gate is in the closed position.

6. The cable clip of claim 2, wherein the catch defines an opening with a top and a bottom and the latch includes a leading edge, a ramped surface and a ledge, the ramped surface configured to engage the top and deflect the latch toward the bottom as the leading edge is inserted through the catch opening, and the top configured to engage the ledge when the gate is in the closed position.

7. The cable clip of claim 6, wherein the outer edge of the second end is adjacent the bottom of the catch when the gate is in the closed position.